


GEEPHON



Portable Digital Signage CBC Series

Widely used in stores, supermarkets, hotels, hospitals and portable scenarios. The slim body and foldable stand take up less space, providing excellent portability

CBC5524B-AA-05




- Slim body
- Narrow bezel Lightweight portable design, low space requirements, easy carry and installation



- Narrow Bezel
- 33mm Narrow bezel, enjoy the borderless View



- Physics Tempered Glass
- The screen is protected by tempered glass to prevent accidental impact damage



- Fail Over™ Support
- Automatically Switches to secondary signal source if primary is lost for continuous display
- Automatic reporting for prompt maintenance, ensuring uninterrupted operation



GalaxyASC
MSC

- CMS / MSC Support(optional)
- Cloud-based remote management (CetusMSC) and CMS platform (GalaxyASC) support
- Real-time monitoring of display status, parameters adjustment, and content distribution
- Remote control via PC and smart phone



- Open API / SDK / RS232 Control
- Supports SDK development and offers OpenAPI interface



- GPlay™ Convenient U disk
- Simply insert the U disk for automatic content copying and playback on the device upon booting



- Victor OTA™ Technology
- Remote update and upgrade of firmware and applications.



- 24/7
- Commercial-grade screen supports 24/7 operation


Specification

Hardware Specification

Display Size	55 inch
Protection Glass	Physics Tempered Glass
Front Color	Black
Set Dimension (L*W*D)	1900 x 747.1 x 47.9mm
Active Display Area (H*V)	1211.4 x 682.2mm
Resolution	3840 x 2160
Type	60Hz E-LED BLU
Brightness(Typ.)	450 cd/m ²
Contrast Ratio(Typ.)	1200:1
Viewing Angle(H/V)	178°(H) x 178°(V)(CR≥10)
Display Colors	1.07G (8bits + FRC)
Color Gamut	72%
Response Time	8ms (Typ)
Operation Hour	24/7
Smart Solution	PTC.DT1AHE-BAB
Connectivity	USB2.0*2, Ethernet(RJ45)*1,
Power	Input Supply: 100-240V AC, 50/60Hz
Power Consumption	130W
Speaker	5W/8Ω *2
Installation	Ground Installation
Package(W*H*D)	2015 x 860 x 165mm
Weight (kg)	TBD
Operating Temperature	0°C ~ +40°C
Storage Temperature	-10°C ~ +60°C

Dimensions

Unit: mm



System Specification


CPU	ARM Quad Core Cortex-A53 1.5G
GPU	Arm Mali-G52 2EE MC1
Operating System	Android 9
Cloud Advertising	Optional
Distribution System	
Cloud Splice System	Optional
Memory	DDR 2G
Storage	EMMC 16GB
Ethernet	Ethernet (RJ45) WiFi 802.11b/g/n 4G LTE(FDD/TDD) (Optional)
Panel Image Rotation	0/90/180/270/360 Angle Rotation
Video Decoder	MPEG-1/2/4, H.264, HEVC, VP8, VP9, AVS+, AVS2, AV1
Audio Decoder	MPEG-1, MPEG-2(layer I/II) MP3, AAC-LC, HE-AAC
Picture Decoding	JPG, JPEG, PNG, BMP

What's in the box

Power Cable	x1
Remote Controller	x1

Warranty

Warranty	Three years or by contract
----------	----------------------------



* Compatibility may differ by equipment.
 * Software compatibility may change over time. Please contact your regional sales representative for details.
 * Specifications are subject to change without notice, so please contact sales team to verify before ordering